facebook

Atale of two labels



Zaid Hammoudi Jose Leitao





Jose Leitao added a new photo 18 mins · 🗱








Comment




Share





Comment



Share










Like



Comment



Share








Comment









Facebook scale

as of December 2016



Facebook scale

as of December 2016



Approximately 85.2% of our daily active users are outside the US and Canada.




Machine to machine


Machine to user

Topology


DR



Topology



Topology



Protocols

ISIS



RSVP-TE (Auto-BW)

BGP

LSPs overview

SF LSPs





S LSPs















Analysis of dropped packets




Investigating their labels



Early findings




Active Probing




LSP with hops and labels



LSP with hops and labels





Bug#1

RFC 4090:

"Upon a failure event, a protected TE LSP is locally repaired by the PLR."


→ Global revertive mode (Headend reoptimizes)


→ Local revertive mode (PLR re-signals)

Bug #1


RFC 4090:


"Upon a failure event, a protected TE LSP is locally repaired by the PLR."







Flag = True



















But this node keeps using the old ones

Adding the label sub-object in the RRO when an LSP is in FRR mode.

bb01.ddd1


bb01.1111



Extract the MP label from the RRO when label is missing from the Node IP address but present in another IP address that belongs to the MP

keeps using

the old ones











Monitor end-to-end

Collect all the things

Failure != Impact

Multivendor is hard



